	SAFETY DATA SHEET	Page : 1 / 14
		Revision nr : 2
		Issue date : 09/03/2015
	BRONZE PASTE WS	Supersedes : 08/07/2013

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation : BRONZE PASTE WS
Product code : 2500, 3000, 3900, 36, 4000, 5000, 6000, 9000, 13000, FT / WS / 80-20, 85-15, 90-10, 95-5
Basic Colour: Rich Gold, Pale Gold, Rich Pale Gold & Deep Gold

1.2. Relevant identified uses of the substance or mixture and uses advised against

Main use category : Industrial uses, Professional uses .

1.3. Details of the supplier of the safety data sheet

Company : AVL METAL POWDERS n.v.
Elleboogstraat 7
B-8500 Kortrijk , Belgium, Europe
Telephone +32 (0)56 22 00 21
Telefax: +32 (0)56 22 64 14
E-mail: sales@avlmetalpowders.com
Website: www.avlmetalpowders.com
VAT: BE 0405 375 371 - RPR Kortrijk

1.4. Emergency telephone number

Emergency telephone : +32 (0)475 38 36 83 (This telephone number is available 24 hours per day, 7 days per week.)

IRELAND (REPUBLIC OF)
National Poisons Information Centre
Beaumont Hospital +353 18 37 99 64/+353 1 809 21 66
UNITED KINGDOM
National Poisons Information Service
(Newcastle Centre) 0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)
Regional Drugs and Therapeutics Centre,
Wolfson Unit

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification according to Regulation (EU) 1272/2008

CLP-Classification : The product is classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

Flam. Sol. 2 H228
STOT SE 3 H336
Aquatic Acute 1 H400
Aquatic Chronic 1 H410

Full text of H-phrases: see section 16

2.1.2. Classification according to EU Directives 67/548/EEC or 1999/45/EC

Classification : This mixture is classified as hazardous according to 1999/45/EC.
F; R11
N; R50/53
R66
R67

	SAFETY DATA SHEET	Page : 2 / 14
		Revision nr : 2
		Issue date : 09/03/2015
	BRONZE PASTE WS	Supersedes : 08/07/2013

Full text of R-phrases: see section 16

2.2. Label elements

2.2.1. Labelling according to Regulation (EU) 1272/2008

Hazard pictograms :



GHS02

GHS07

GHS09

Signal word :

Warning

Contains :

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hazard statements :

H228 - Flammable solid.

H336 - May cause drowsiness or dizziness.

H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 - Ground/bond container and receiving equipment.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Extra phrases :

EUH066 - Repeated exposure may cause skin dryness or cracking.

2.2.2. Labelling according to Directives (67/548 - 1999/45)

Not relevant

2.3. Other hazards

Other hazards :

PBT/vPvB data :

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Substance name	Product identifier	%	Classification according to Directive 67/548/EEC
copper	(CAS No.) 7440-50-8 (EC No) 231-159-6 (REACH-no) 01-2119480154-42-XXXX	55 - 90	N; R50 R53
Zinc	(CAS No.) 7440-66-6 (EC No) 231-175-3 (EC Index) 030-001-01-9 (REACH-no) 01-2119467174-37-XXXX	5 - 30	N; R50/53
hydrocarbons, c9-c11, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC No) 919-857-5 (REACH-no) 01-2119463258-33-XXXX	5 - 20	R10 Xn; R65 R66 R67

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
copper	(CAS No.) 7440-50-8 (EC No) 231-159-6 (REACH-no) 01-2119480154-42-XXXX	55 - 90	Aquatic Acute 1, H400 (M=10) Aquatic Chronic 3, H412

	SAFETY DATA SHEET	Page : 3 / 14
		Revision nr : 2
		Issue date : 09/03/2015
	BRONZE PASTE WS	Supersedes : 08/07/2013

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Zinc	(CAS No.) 7440-66-6 (EC No) 231-175-3 (EC Index) 030-001-01-9 (REACH-no) 01-2119467174-37-XXXX	5 - 30	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
hydrocarbons, c9-c11, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC No) 919-857-5 (REACH-no) 01-2119463258-33-XXXX	5 - 20	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	: Provide fresh air. Keep at rest. When in doubt or if symptoms are observed, get medical advice.
Skin contact	: Remove contaminated clothing and shoes. Wash with plenty of water/. When in doubt or if symptoms are observed, get medical advice. Wash contaminated clothing before reuse.
Eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician if irritation develops or persists.
In case of ingestion	: Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get medical advice/attention.
Additional advice	: First aider: Pay attention to self-protection! See also section 8 Treat symptomatically. Show this safety data sheet to the doctor in attendance. When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	: Vapours may cause drowsiness and dizziness. Repeated or prolonged exposure: (dust) : May cause respiratory irritation. The following symptoms may occur: Headache, Nausea, Unconsciousness.
Skin contact	: Prolonged skin contact may defat the skin and produce dermatitis. Repeated exposure may cause skin dryness or cracking. The following symptoms may occur: erythema (redness), Dry skin.
Eye contact	: Dust contact with the eyes can lead to mechanical irritation.
Ingestion	: May be irritating.
Other adverse effects	: none.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam, ABC-powder, Carbon dioxide, Dry sand
Extinguishing media which must not be used for safety reasons:	: Water

	SAFETY DATA SHEET	Page : 4 / 14
		Revision nr : 2
		Issue date : 09/03/2015
	BRONZE PASTE WS	Supersedes : 08/07/2013

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable solid
- Specific hazards : Vapours can form explosive mixtures with air.
Vapours are heavier than air and may spread along floors.
Beware of reignition.
The pressure in sealed containers can increase under the influence of heat.
Burning produces noxious and toxic fumes.
Hazardous decomposition products COx
metal oxides
Do not allow run-off from fire-fighting to enter drains or water courses.
Dispose according to legislation.

5.3. Advice for firefighters

- Advice for firefighters : Special protective equipment for firefighters.
In case of fire: Wear self-contained breathing apparatus.
Use water spray jet to protect personnel and to cool endangered containers.
Evacuate area.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel : Evacuate area.
Provide adequate ventilation.
Use personal protective equipment as required.
Personal protection equipment: see section 8
Avoid contact with skin, eyes and clothes.
Avoid generation of dust.
Do not breathe vapours/dust.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.
Use only non-sparking tools.
- For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place.
Personal protection equipment: see section 8.

6.2. Environmental precautions

- Environmental precautions : Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Stop leak if safe to do so.
Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
Collect in closed and suitable containers for disposal.
Dispose according to legislation.
Site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

6.4. Reference to other sections

- Personal protection equipment: see section 8
Disposal: see section 13.

	SAFETY DATA SHEET	Page : 5 / 14
		Revision nr : 2
	BRONZE PASTE WS	Issue date : 09/03/2015
		Supersedes : 08/07/2013

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Handling :
- Use only in well-ventilated areas.
 - Provide adequate ventilation.
 - Use personal protective equipment as required.
 - Personal protection equipment: see section 8 .
 - Avoid contact with skin, eyes and clothes.
 - Avoid generation of dust.
 - Do not breathe vapours/dust.
 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - Take precautionary measures against static discharges.
 - Ensure that the equipment is adequately grounded.
 - Take any precaution to avoid mixing with incompatible materials.
 - See also section 10
 - Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time).
 - Do not allow to enter into surface water or drains.
- Advices on general occupational hygiene :
- Keep good industrial hygiene.
 - When using do not eat, drink or smoke.
 - Wash hands before breaks and immediately after using the product.
 - Take off contaminated clothing.

7.2. Conditions for safe storage, including any incompatibilities

- Storage :
- Flammable solids
 - Keep container tightly closed in a cool, well-ventilated place.
 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - Protect from sunlight.
 - Protect from moisture.
 - Do not store near or with any of the incompatible materials listed in section 10.
 - Maximum storage period (time) :
 - 3 months.
- Packaging materials :
- Keep/Store only in original container.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limit values :

copper (7440-50-8)		
Austria	MAK (mg/m ³)	1 mg/m ³ (inhalable fraction) 0,1 mg/m ³ (respirable fraction, smoke)
Austria	MAK Short time value (mg/m ³)	4 mg/m ³ (inhalable fraction) 0,4 mg/m ³ (respirable fraction, smoke)
Belgium	Limit value (mg/m ³)	0,2 mg/m ³ (fume) 1 mg/m ³ (dust and mist)
Bulgaria	OEL TWA (mg/m ³)	0,1 mg/m ³ (metal vapor)
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	0,2 mg/m ³ (fume) 1 mg/m ³ (dust)
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	2 mg/m ³ (dust and fumes)

	SAFETY DATA SHEET		Page : 6 / 14
			Revision nr : 2
	BRONZE PASTE WS		Issue date : 09/03/2015
			Supersedes : 08/07/2013

copper (7440-50-8)		
France	VLE (mg/m ³)	2 mg/m ³ (dust)
France	VME (mg/m ³)	0,2 mg/m ³ (fume) 1 mg/m ³ (dust)
Greece	OEL TWA (mg/m ³)	0,2 mg/m ³ (fume) 1 mg/m ³ (dust)
Greece	OEL STEL (mg/m ³)	2 mg/m ³ (dust)
Italy - Portugal - USA ACGIH	ACGIH TWA (mg/m ³)	0,2 mg/m ³ (fume)
Latvia	OEL TWA (mg/m ³)	0,5 mg/m ³
Spain	VLA-ED (mg/m ³)	0,2 mg/m ³ (fume) 1 mg/m ³ (dust and mist)
Switzerland	VLE (mg/m ³)	0,2 mg/m ³ (inhalable)
Switzerland	VME (mg/m ³)	0,1 mg/m ³ (inhalable)
Netherlands	Grenswaarde TGG 8H (mg/m ³)	0,1 mg/m ³ (inhalable fraction)
United Kingdom	WEL TWA (mg/m ³)	1 mg/m ³ (dust and mists) 0,2 mg/m ³ (fume)
United Kingdom	WEL STEL (mg/m ³)	0,6 mg/m ³ (calculated-fume) 2 mg/m ³ (dust and mist)
Czech Republic	Expoziční limity (PEL) (mg/m ³)	1 mg/m ³ (dust) 0,1 mg/m ³ (fume)
Denmark	Grænseværdie (langvarig) (mg/m ³)	1,0 mg/m ³ (dust and powder) 0,1 mg/m ³ (fume)
Finland	HTP-arvo (8h) (mg/m ³)	1 mg/m ³ 0,1 mg/m ³ (respirable dust and fume)
Hungary	AK-érték	1 mg/m ³ 0,1 mg/m ³ (fume)
Hungary	CK-érték	4 mg/m ³ 0,4 mg/m ³ (fume)
Ireland	OEL (8 hours ref) (mg/m ³)	0,2 mg/m ³ (fume) 1 mg/m ³ (dust and mist)
Ireland	OEL (15 min ref) (mg/m ³)	0,6 mg/m ³ (calculated-fume) 2 mg/m ³ (dust and mist)
Lithuania	IPRV (mg/m ³)	1 mg/m ³ (inhalable fraction) 0,2 mg/m ³ (respirable fraction)
Norway	Gjennomsnittsverdier (AN) (mg/m ³)	0,1 mg/m ³ (fume) 1 mg/m ³ (dust)
Norway	Gjennomsnittsverdier (Korttidsverdi) (mg/m ³)	0,3 mg/m ³ (fume) 3 mg/m ³ (dust)
Poland	NDS (mg/m ³)	0,2 mg/m ³
Romania	OEL TWA (mg/m ³)	0,50 mg/m ³ (powder)
Romania	OEL STEL (mg/m ³)	0,20 mg/m ³ (fume) 1,50 mg/m ³ (dust)
Slovakia	NPHV (priemerná) (mg/m ³)	1 mg/m ³ (dust) 0,1 mg/m ³ (fume)
Slovakia	NPHV (Hraničná) (mg/m ³)	2 mg/m ³ (dust) 0,2 mg/m ³ (fume)
Sweden	nivågränsvärde (NVG) (mg/m ³)	1 mg/m ³ (total dust) 0,2 mg/m ³ (respirable dust)

Zinc (7440-66-6)		
Switzerland	VLE (mg/m ³)	0,4 mg/m ³ (respirable)

	SAFETY DATA SHEET	Page : 7 / 14
	BRONZE PASTE WS	Revision nr : 2
		Issue date : 09/03/2015
		Supersedes : 08/07/2013

Zinc (7440-66-6)		
Switzerland	VME (mg/m ³)	0,1 mg/m ³ (respirable) 2 mg/m ³ (inhalable)

Recommended monitoring procedures : Concentration measurement in air
Personal air monitoring


8.2. Exposure controls

- Personal protection equipment : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
Half-face mask (DIN EN 140) (EN 140)
Full face mask (EN 136) (EN 136)
Filter type: A/P (EN 141)
- Hand protection : Wear chemically resistant gloves (tested to EN374) .,The selection of specific gloves for a specific application and time of use in a working area, should also take into account other factors on the working space, such as (but not limited to): other chemicals that are possibly used, physical requirements (protection against cutting/drilling, skill, thermal protection), and the instructions/specification of the supplier of gloves.,Breakthrough time (maximum wearing time) : >480 ',NBR (Nitrile rubber)
- Eye protection : Tightly fitting safety goggles (EN166). Wear eye glasses with side protection according to EN 166.
- Body protection : Wear suitable protective clothing.
Chemical resistant safety shoes
Wear suitable coveralls to prevent exposure to the skin.
- Thermal hazard protection : Not required under normal use.
- Engineering control measures : Provide adequate ventilation.
Use only in area provided with appropriate exhaust ventilation.
A washing facility/water for eye and skin cleaning purposes should be present.
Ensure that the equipment is adequately grounded.
Take precautionary measures against static discharges.
Organisational measures to prevent/limit releases, dispersion and exposure
See also section 7
- Environmental exposure controls : Do not allow to enter into surface water or drains.
Comply with applicable Community environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Appearance : Paste
- Colour : bronze
- Odour : slight, Petroleum
- Odour threshold: : No data available
- Odour threshold: : No data available
- pH : Not applicable
- Melting point/freezing point : 850 °C bronze

	SAFETY DATA SHEET	Page : 8 / 14
		Revision nr : 2
		Issue date : 09/03/2015
	BRONZE PASTE WS	Supersedes : 08/07/2013

Initial boiling point and boiling range	: 2300 °C bronze 130 - 210 °C Solvent
Flash point	: > 36 °C Solvent (ASTM D-86)
Evaporation rate	: 0,14 Solvent (n-butyl acetate = 1)
Flammability (solid, gas)	: Flammable.
Upper/lower flammability or explosive limits	: LEL: 0,6 vol % Solvent UEL: 7 vol % Solvent
Vapour pressure	: (20°C) 0,3 kPa Solvent
Vapour density	: (Air = 1) > 1 Solvent
Density	: (20 °C) 7,14 - 8,96 g/cm ³ bronze (15 °C) 740 - 850 kg/m ³ Solvent
Relative density	: (Water=1) 0,7 kg/l bronze (Water=1) (15 °C) 0,741 - 0,851 Solvent
Water solubility	: Insoluble
Solubility in different media	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: > 200 °C Solvent
Decomposition temperature	: No data available
Viscosity	: (20 °C) 0,8 - 2,1 cSt Solvent
Explosive properties	: Not applicable The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidising properties	: Not applicable The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity : Flammable solid.
Reference to other sections: 10.5

10.2. Chemical stability

Stability : The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions : Vapours can form explosive mixtures with air.
Reference to other sections: 10.4 & 10.5

10.4. Conditions to avoid

Conditions to avoid : Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.
Avoid generation of dust.
See also section 7
Handling and storage

	SAFETY DATA SHEET	Page : 9 / 14
		Revision nr : 2
	BRONZE PASTE WS	Issue date : 09/03/2015
		Supersedes : 08/07/2013

10.5. Incompatible materials

Incompatible materials : Acids and bases ., Oxidising substances ., Halogens, Halogenated compounds ., See also section 7, Handling and storage

10.6. Hazardous decomposition products

Hazardous decomposition products : Carbon oxides, metal oxides Reference to other sections: 5.2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified (Based on available data, the classification criteria are not met.)

Zinc (7440-66-6)	
LD50/oral/rat	2000 mg/kg (OECD 401)
LC50/inhalation/4h/rat	> 5,41 mg/m ³ (OECD 403)
ATE CLP (oral)	2000 mg/kg bodyweight

hydrocarbons, c9-c11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LD50/oral/rat	> 5000 mg/kg OECD 401
LD50/dermal/rabbit	> 5000 mg/kg OECD 402
LC50/inhalation/4h/rat	4951 mg/m ³ OECD 403

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met.)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics :
Repeated exposure may cause skin dryness or cracking
pH: Not applicable

Serious eye damage/eye irritation : Not classified (Based on available data, the classification criteria are not met.)
pH: Not applicable

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met.)

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met.)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met.)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met.)

STOT-single exposure : May cause drowsiness or dizziness.
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics :
May cause drowsiness or dizziness

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met.)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met.)

Other information

Symptoms related to the physical, chemical and toxicological characteristics, Reference to other sections: 4.2

SECTION 12: Ecological information

12.1. Toxicity

Toxicity : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

	SAFETY DATA SHEET	Page : 10 / 14
		Revision nr : 2
		Issue date : 09/03/2015
	BRONZE PASTE WS	Supersedes : 08/07/2013

copper (7440-50-8)	
LC50 fish 1	0,0068 - 0,0156 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	0,03 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	< 0,3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 72h algae [mg/l] (1)	0,0426 - 0,0535 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h algae [mg/l] (1)	0,031 - 0,054 mg/l (Species: Pseudokirchneriella subcapitata [static])

Zinc (7440-66-6)	
LC50 fish 1	439 µg/l Cottus bairdii (pH 6-6.5) 780 µg/l Pimephales promelas (fathead minnow) (pH 7-7.5) 330 µg/l Pimephales promelas (fathead minnow) (pH 8- 8.5) 500 µg/l Pimephales promelas (fathead minnow)
EC50 Daphnia 1	2909 - 2140 µg/l (OECD 202)
EC50 other aquatic organisms 1	(OECD 202) 0,937 mg/l Poecilia reticulata (Guppy) (OECD 202) 0,416 mg/l Ceriodaphnia Dubia (water flea)
EC50 72h algae [mg/l] (1)	0,09 - 0,125 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h algae [mg/l] (1)	0,11 - 0,271 mg/l (Species: Pseudokirchneriella subcapitata [static])
LOEC (chronic)	240 µg/L Pimephales promelas (fathead minnow)
NOEC chronic fish	(30d) 169 µg/L Cottus bairdii
Additional information	NOEC, aquatic invertebrates, long term, Ceriodaphnia Dubia (water flea): 25 µg/L (7 days, freshwater) NOEC, aquatic invertebrates, long term, Daphnia magna (Big water flea): 100 µg/L (3 weeks, freshwater) NOEC, aquatic invertebrates, long term, Mytilus edulis: 75 µg/L (3 days, freshwater) NOEC, aquatic algae, Pseudokirchneriella subcapitata: 24 µg/L (72 hours, OECD 201) LOAEC, aquatic algae, Nitzschia closterium: 20 µg/L (4 days)

hydrocarbons, c9-c11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Additional information	EL0, Daphnia magna (Big water flea), acute: 1000 mg/l (48 hours) NOELR, Pseudokirchneriella subcapitata, acute: 100 mg/l (72 hours) EL50, Pseudokirchneriella subcapitata, acute: >1000 mg/l (72 hours) LL50, acute, Oncorhynchus mykiss (Rainbow trout): >1000 mg/l (96 hours)

12.2. Persistence and degradability

Persistence and degradability : Solvent
Readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulation : No data available
Partition coefficient n-octanol/water : No data available

12.4. Mobility in soil

Mobility : No data available

12.5. Results of PBT and vPvB assessment

PBT/vPvB data : PBT/vPvB data
This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).
This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

	SAFETY DATA SHEET	Page : 11 / 14
		Revision nr : 2
		Issue date : 09/03/2015
	BRONZE PASTE WS	Supersedes : 08/07/2013

12.6. Other adverse effects

Other information :

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product waste: : Handle with care.
Safe handling: see section 7
Handling and storage
Collect and dispose of waste product at an authorised disposal facility.
Refer to manufacturer/supplier for information on recovery/recycling.
If recycling is not practicable, dispose of in compliance with local regulations.
Dispose according to legislation.

Contaminated packaging : If recycling is not practicable, dispose of in compliance with local regulations.
Empty containers should be taken to local recyclers for disposal.
Do not burn, or use a cutting torch on, the empty drum.
Do not puncture or incinerate.

Further ecological information : Do not allow to enter into surface water or drains.

List of proposed waste codes/waste designations in accordance with EWC : Classified as hazardous waste according to European Union regulations.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

SECTION 14: Transport information

14.1. UN number

UN number : 1325

14.2. UN proper shipping name

Proper Shipping Name : FLAMMABLE SOLID, ORGANIC, N.O.S. (Copper/Zinc/Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

Proper shipping name IATA/IMDG : FLAMMABLE SOLID, ORGANIC, N.O.S. (Copper/Zinc/Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

14.3. Transport hazard class(es)

14.3.1. Overland transport

Class(es) : 4.1 - Flammable solids, self-reactive substances and solid desensitized explosives
Hazard identification number (Kemler No.) : 40
Classification code : F1
ADR/RID-Labels : 4.1 - Flammable solid



14.3.2. Inland waterway transport (ADN)

Class (UN) : 4.1

14.3.3. Transport by sea

Class or Division : 4.1 - Flammable solids, self-reactive substances and solid desensitized explosives

14.3.4. Air transport

Class or Division : 4.1 - Flammable solids, self-reactive substances and solid desensitized explosives

14.4. Packing group

Packing group : II

	SAFETY DATA SHEET	Page : 12 / 14
		Revision nr : 2
		Issue date : 09/03/2015
	BRONZE PASTE WS	Supersedes : 08/07/2013

14.5. Environmental hazards

Environmental hazards : N



Other information : No supplementary information available.

14.6 Special precautions for user No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006 :

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008 : hydrocarbons, c9-c11, n-alkanes, isoalkanes, cyclics, <2% aromatics

40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not. : BRONZE PASTE WS - hydrocarbons, c9-c11, n-alkanes, isoalkanes, cyclics, <2% aromatics

This product contains an ingredient according to the candidate list of Annex XIV of the REACH Regulation 1907/2006/EC. : None

Authorisations : Not applicable

15.1.2. National regulations

DE : WGK : 2
 DE : German storage class (LGK) : LGK 4.1B - Flammable solids
 DE : Technische Regeln für Gefahrstoffe (TRGS) : applicable
 FR : Installations classées : 1450;117x
 NL : ABM : 4 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. A/B

15.2. Chemical safety assessment

Chemical Safety Assessment : For the following substances of this preparation a chemical safety assessment has been carried out:
 Copper
 Zinc
 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

	SAFETY DATA SHEET	Page : 13 / 14
		Revision nr : 2
		Issue date : 09/03/2015
	BRONZE PASTE WS	Supersedes : 08/07/2013

SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Aquatic Acute 1	: Hazardous to the aquatic environment - Aquatic Acute 1
Aquatic Chronic 1	: Hazardous to the aquatic environment - chronic hazard category 1
Aquatic Chronic 3	: Hazardous to the aquatic environment - chronic hazard category 3
Asp. Tox. 1	: Aspiration hazard, Category 1
Flam. Liq. 3	: Flammable liquids, Category 3
Flam. Sol. 2	: Flammable solids, Category 2
STOT SE 3	: Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	: Flammable liquid and vapour.
H228	: Flammable solid.
H304	: May be fatal if swallowed and enters airways.
H336	: May cause drowsiness or dizziness.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
R10	: Flammable.
R11	: Highly flammable.
R50	: Very toxic to aquatic organisms.
R50/53	: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53	: May cause long-term adverse effects in the aquatic environment.
R65	: Harmful: may cause lung damage if swallowed.
R66	: Repeated exposure may cause skin dryness or cracking.
R67	: Vapours may cause drowsiness and dizziness.
F	: Highly flammable
N	: Dangerous for the environment
Xn	: Harmful

Key literature references and sources for data : European Metal Particulate Association (EMPA)
Supplier SDS

Abbreviations and acronyms : ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods Code
LEL = Lower Explosive Limit/Lower Explosion Limit
UEL = Upper Explosion Limit/Upper Explosive Limit
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
TWA = time weighted average
STEL = Short term exposure limit
PBT = persistent, bioaccumulating and toxic (PBT).
vPvB = very persistent and very bioaccumulating
EWC = European Waste Catalogue
NA = Not applicable
LC50 = Median lethal concentration
LD50 = Median lethal dose
EC50 = Median Effective Concentration
N.O.S. = Not Otherwise Specified
WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

The contents and format of this SDS are in accordance with EEC Commission Directive 1999/45/EC, 67/548/EC, 1272/2008/EC and EEC Commission Regulation 1907/2006/EC (REACH) Annex II.

	SAFETY DATA SHEET	Page : 14 / 14
	BRONZE PASTE WS	Revision nr : 2
		Issue date : 09/03/2015
		Supersedes : 08/07/2013

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.